

Rheological characteristics of filamentous cultivation broths and suitable model systems

C. Bliatsiou[▲], K. Pommerehne^{*♦}, P. Waldherr[▲], S. Tesche^{*♦}, L. Böhm[▲], R. Krull^{*♦}, M. Kraume[▲]

Technische Universität Berlin | [▲]Chair of Chemical and Process Engineering

Technische Universität Braunschweig | ^{*}Institute of Biochemical Engineering | [♦]Center of Pharmaceutical Engineering

Background and motivation


Aim: Rheological characterization of biological systems and establishment of a database for the rheological modeling of these cultivation broths for any possible use in the field of fluid dynamics and (bio)process engineering.

- Filamentous microorganisms show a diverse morphology (e.g. freely dispersed mycelia, dense pellets).
- Rheology influences mixing and mass transport → impact on overall performance of cultivation process.
- Studied filamentous microorganisms: a) fungus *Aspergillus niger*, bacteria b) *Lechavalieria aerocolonigenes*, and c) *Actinomadura namibiensis*.
- Model Fluids facilitate experimental research (e.g. fluid dynamic examinations).
- Non-biological model fluids compared with flow behavior of examined filamentous microorganisms.


Measurement systems

- Biomass-containing samples: rotational rheometer Malvern, Kinexus lab+ with vane
- Model fluids: rotational rheometer Anton Paar, MCR 302 with cone-plate system
- Curve fitting according to the Ostwald–de Waele power law:

$$\tau = K \cdot \dot{\gamma}^n$$



Influence of the biomass concentration on rheological parameters




Non-biological model fluids

- μ [Pa·s] = $f(X$ [g/kg]) ; K [Pa·sⁿ] = $f(X$ [g/kg]) ; n [-] = $f(X$ [g/kg])

Model system	Rheological behavior	Range of concentration X	Rheological model	Modeled range of shear rates $\dot{\gamma}$
Glycerol	newtonian	10-1000 g/kg	$\mu=0.0006 \cdot e^{0.0064 \cdot X}$	1-1000 s ⁻¹
Invert sugar sirup		10-1000 g/kg	$\mu=0.0005 \cdot e^{0.0056 \cdot X}$	1-1000 s ⁻¹
Polyvinylpyrrolidone (Luviskol® BASF)		10-200 g/kg	$\mu=0.0033 \cdot e^{0.0337 \cdot X}$	1-1000 s ⁻¹
Polyethyleneglycol (PEO/PEG)	shear thinning	20-300 g/kg	Ostwald-de Waele power law $K=5 \cdot 10^{-7} \cdot X^{2.93}$, $n=0.9632 \cdot e^{-0.003 \cdot X}$	100-1000 s ⁻¹
Carboxymethyl cellulose (CMC)		0.1-10 g/kg	Ostwald-de Waele power law $K=0.1144 \cdot X^{1.2105}$, $n=0.7417 \cdot e^{-0.05 \cdot X}$	10-1000 s ⁻¹
Xanthan gum solution		0.5-10 g/kg	Ostwald-de Waele power law $K=0.3591 \cdot X^{1.09}$, $n=0.3707 \cdot X^{-0.124}$	1-1000 s ⁻¹

Rheological modeling of filamentous cultivation broths



Conclusions and further challenges

- Vane (impeller) **measuring system** preferable for mycelial biomass, but fails for low and high shear rates due to sedimentation and turbulence effects, respectively.
- Increased viscosity of cultivations broths results from presence of microorganisms.
- Flow consistency factor K increases with **biomass concentration**, flow behavior index n is independent of biomass.
- Xanthan most suitable **model fluid** for *A. niger* and *A. namibiensis*. Low viscous shear thinning behavior of *L. aerocolonigenes* not successfully modeled yet.
- Newtonian cultivation broths consisting mainly of pellets and rheological elastic characteristics of the examined systems not part of the investigation so far.

Acknowledgement

The authors gratefully acknowledge financial support from the German Research Foundation (DFG) in the Priority Programme 1934 DiSPBiotech – Dispersity, structural and phase modifications of proteins and biological agglomerates in biotechnological processes.